

DIP - Switch Schalterstellungen für Tachoanpassung

6-poliger DIP - Switch, 1 = on, 0 = off

Fahrzeug: IVECO 40 - 10 W Bj. 1989 Getriebe Typ 2822 Achsübersetzung 1:5,22

Reifengröße	Schalterstellung (1-6)	Tachoabweichung	mittl. Abrollumfang [mm]
7.50R16	0 1 0 1 1 1		2450
8.25R16	0 1 1 1 0 0	-2,3%	2625
8.25R16	0 1 1 1 0 1	0 ... 0,6%	
9.00R16	1 0 0 0 1 1	0 ... 2,0%	2780
9.00R16	1 0 0 1 0 0	2,0 ... 4,0%	
9.00R16	1 0 0 1 0 1	4,0 ... 5,0%	
235/85 R16			2445
255/100 R16			2780
255/85 R16			2580
265/75 R16	0 1 0 1 1 1	+/- 0,5%	2460
285/75 R16			2550

Reto 010111 (255/100)

10-poliger DIP - Switch, 1 = on, 0 = off Fahrtenschreibertacho

Fahrzeug: IVECO 40 - 10 W ab Bj. 1990 Getriebe Typ Achsübersetzung 1:5,22

Reifengröße	Schalterstellung (1-10)	Tachoabweichung	mittl. Abrollumfang [mm]
7.50R16			2450
8.25R16			2625
8.25R16			
9.00R16	0 0 1 0 0 1 0 0 1 0		2780
9.00R16			
9.00R16			
235/85 R16			2445
255/100 R16			2780
255/85 R16	0 0 0 0 1 1 1 1 0 0		2580
265/75 R16			2460
285/75 R16			2550

8-poliger DIP - Switch, 1 = on, 0 = off

Fahrzeug: IVECO 40 - 10 W ab Bj. 1990 Getriebe Typ Achsübersetzung 1:5,22

Reifengröße	Schalterstellung (1-8)	Tachoabweichung	mittl. Abrollumfang [mm]
7.50R16	0 1 0 0 1 1 0 1		2450
8.25R16			2625
8.25R16			
9.00R16	0 0 1 1 0 1 0 0		2780
9.00R16			
9.00R16			
235/85 R16			2445
255/100 R16			2780
255/85 R16			2580
265/75 R16			2460
285/75 R16			2550

20	0 1 0 0 1 1	
----	-------------	--

21	0 1 0 1 0 0	
22	0 1 0 1 0 1	
23	0 1 0 1 1 0	
24	0 1 0 1 1 1	7.50 R16
25	0 1 1 0 0 0	
26	0 1 1 0 0 1	
27	0 1 1 0 1 0	
28	0 1 1 0 1 1	
29	0 1 1 1 0 0	8.25 R16 Tacho 0 ... 2,3%
30	0 1 1 1 0 1	8.25 R16 Tacho 0 ... 0,6%
31	0 1 1 1 1 0	
32	0 1 1 1 1 1	
33	1 0 0 0 0 0	
34	1 0 0 0 0 1	
35	1 0 0 0 1 0	
36	1 0 0 0 1 1	9.00 R16 Tacho 0 ... 2% km -0,5%
37	1 0 0 1 0 0	9.00 R16 Tacho 2 ... 4% km +1,5%
38	1 0 0 1 0 1	9.00 R16 Tacho 4 ... 5% km +4,5%